

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Dave M. Thomas, Jr.

3. ADDRESS OF OPERATOR Walsh Engr. & Prod.

PO Drawer 419, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

790' FSL + 1850' FEL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF

☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
OCT 20 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE

Jicarilla Contract #413

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chacon Jicarilla

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Ballard Pictured Cliff Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15-T23N-R3W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3339 GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SEE ATTACHED

RECEIVED
JAN 29 1985

OIL CON. DIV.
DIST. 3

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dewayne Blancett

TITLE Production Foreman October 13, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED

NOV 1 1984

M. MILLENBACH
AREA MANAGER

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

(See Instructions on Reverse Side)

NMOCC



DAVE M. THOMAS, JR.
CHACON JICARILLA NO. 2
SECTION 15-T23N-R3W
RIO ARIBA COUNTY, NEW MEXICO

17 Continued:

Formation Tops:

Ojo Alamo	2650'
Kirtland	2850'
Fruitland	2986'
Picture Cliffs	3080'
Lewis	3135'

9 5/8" 32 lb. set at 138'
4 1/2" 9.5 lb. set at 3248.

Well was plugged in following manner:

10/1/82 Spot cement plug from 3152' to 2800" w/ 28 sacks
Class "B" cement.

Spot cement plug from 2700' to 2500' w/ 15 sacks
Class "B" cement.

* Pull 6 joints 4 1/2" 10.5 casing.

Spot cement plug from 350' to 180' w/ 25 sacks
Class "B" cement.

Spot cement plug from 180' to surface w/ 45 sacks
Class "B" cement.

Install dry hole marker, w/ 12 sacks cement, pull
deadman anchors, clean location.

Verbal approval was given by R. Bell on 9/21/82
to spot cement 50' inside and 50' on top of
4 1/2" casing stub at 271', 180' of 4 1/2" casing
in hole was removed and a cement plug spotted
from 180' to surface.

* Approximately 90' of 4 1/2" casing was removed
from well several years ago in an attempt
to repair a casing leak at 271'.
Per Bill McCown w/ Walsh Engineering.
R. Bell
10/20/82