Form 9-331 (May 1963)

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

UNITED STATES UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

FRACTURE TREATMENT

(Other)

SHOOTING OR ACIDIZING

Form approved. 5. LEASE DESIGNATION AND SERIAL NO.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

	Lease Co	Lease Contract#40		
SUNDR (Do not use this form	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache			
OIL GAS X OTHER Drilling		7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR	8, FARM OR LEASE NAME			
Amerada Hess Co	J. Apache "D"			
3. ADDRESS OF OPERATOR		9. WELL NO.	9. WELL NO.	
P.O. Box 2040,	Tulsa, Oklahoma 74102	2		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		Otero: B. Dákota Pictured Cliff		
1650' FWL and 990' FSL		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 2, T23N, R5W		
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE		
	Gr. 6736'	Rio Arriba	N. Mexico	
16.	Check Appropriate Box To Indicate Nature of Notice, Report,	or Other Data		
NOTIO	E OF INTENTION TO:	UBSEQUENT REPORT OF:		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) Spudding 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in Cactus Drilling Co. rig #19 and spudded a 12-1/4" hole at 5:30 AM 6/13/76, drilled to 352', run, set and cemented 8-5/8"OD 24# K-55 smls. new casing at 349' with a total of 245 sx. Class B cement by Halliburton, cement in place at 6:35 PM 6/13/76 W/700# PP, circ. cement to surface, WOC until 7:30 AM 6/14 and tested csg. to 1000# 0.K., started drilling a 7-7/8" hole out under 8-5/8" csg. @ 9 AM 6/14/76



	The second of th	
8. I hereby certify that the foregoing is true and correct	TITLE Supervisor, Drlg. Adm. Serv bate	June 15, 1976
(This space for Federal of State office use)		
APPROVED BY	TITLE DATE _	