Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Jic. #167

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jic. Apache

7. UNIT AGREEMENT NAME

1.
OIL WELL ☐   GAS WELL ☒   OTHER

8. FARM OR LEASE NAME

Jic. Apache "I"

2. NAME OF OPERATOR

Amerada Hess Corporation

9. WELL NO.

4

3. ADDRESS OF OPERATOR

Box 2040 – Tulsa, Oklahoma 74102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

890' FSL, 890' FWL

So. Blanco Otero: Picture Cliff
Chacon Otero: Dakota

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 11, T23N, R3W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Est. 7205' GL

12. COUNTY OR PARISH   13. STATE

Rio Arriba   New Mexico

16.   **Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data**

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other)   Spudding

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☒ XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) _____
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Moved in and rigged up Aztec Rig #124 and spudded 13-3/4" hole at 8:00 PM 4/14/77 and drilled to 381'. Ran, set and cemented 9-5/8" OD 32# H40 New SS Csg. at 381' with 350 sx. cement by Dowell Inc. Circ. approx. 100 sx. cement.

Trip in hole with bit. Tested csg. with 1000#, O.K. and started drilling out ;under 9-5/8" OD Csg. at 11:45 PM 4/15/77 with 8-3/4" bit.

18. I hereby certify, that the foregoing is true and correct

SIGNED _H. O. Porter_   TITLE Admin. Assist. Drlg. Svcs.   DATE 5/2/77

(This space for Federal or State office use)

APPROVED BY _____   TITLE _____   DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side