

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

Contact No. 412

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chacon Jicarilla

9. WELL NO.

11

10. FIELD AND POOL, OR WILDCAT

Ballard P.C.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 16-T23N-R3W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

Rio Arriba

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Dave M. Thomas, Jr.

3. ADDRESS OF OPERATOR

P. O. Box 2026, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1850'FNL, 1850'FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7363'G.L., 7374'D.F., 7375'K.B.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

6-30-78 Spud well

6-30-78 T.D. 100'

Ran 3 jts., 8-5/8", 24.0 lb., K-55 casing (86.50')
Set at 98.50' with 125 sacks Class "B" cement with
3% KCl and 1/4 lb. Flocele per sack. Cement Cir-
culated. Pressure test with 500 psig. Test O.K.

7-3-78 T.D. 3263'

Ran 94 jts., 4 1/2", 10.50 lbs., K-55 casing (3239.26')
Set at 3249.26' with 500 gallons mud flush followed
by 190 sacks 50-50 Pozmix with 6 1/4 lbs. Gilsonite
and 6 lbs. salt per sack.

FOR: Dave M. Thomas, Jr.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ewell N. Walsh, P.E.

TITLE

President, Walsh Engr.
& Production Corp.

DATE

7-6-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUL 10 1978

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.