

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR ARCO Oil and Gas Company
Division of Atlantic Richfield Company

3. ADDRESS OF OPERATOR Suite 501 Lincoln Tower
1860 Lincoln Street, Denver, Colorado 80295

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17
below.)

AT SURFACE: 1840' FSL & 1840' FWL (NE SW)

AT TOP PROD. INTERVAL: Unit K

AT TOTAL DEPTH: Approx. the same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) N.O. spud and setting surface casing		

5. LEASE

Joint Venture

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Apache JV 5

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

Chacon Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA

5-23N-3W

12. COUNTY OR PARISH 13. STATE

Rio Arriba-

New Mexico

14. API NO.

30-029-22014

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7272' GL

7283' KB

(NOTE: Report results of multiple completion or zone
change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU. Spud 5:00 p.m. 8-9-79. Cemented 8 jts. 8-5/8" 24#, K-55, ST&C
R-3 new casing with GS (329') and landed @ 306' KB. (KB-GL 13').
Pressure tested blind rams and pipe rams to 1000# for 30 minutes,
held OK. Cemented with 300 sks Class "B", 2% CaCl, 1/4#/sk flocele.

Drilling ahead.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct Operations

Manager

SIGNED W. A. Walther, Jr.

TITLE

DATE

10-9-79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: