

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Contract No. 412

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chacon Jicarilla Apache "D"

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Chacon Dakota Associated Pox

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 16-T23N-R3W

N.M.P.M.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Dave M. Thomas, Jr.

3. ADDRESS OF OPERATOR
P. O. Box 2026 Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
790'FSL, 1850'FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
7409'GR, 7422'DF, 7423'KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recombination Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/14/80 Spud Well

2/15/80 T.D. 285'. Ran 8 joints 8-5/8", 24.0 lb., K-55 casing (262.94') set at 274.94' with 275 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement Circulated approximately 5 barrels. Pressure test with 500 psig. Test ok.

2/28/80 T. D. 7725'. Ran 224 joints 4-1/2", 10.50 & 11.60, K-55 casing (7683.05') set at 7697.05' with:

First Stage: 440 sacks 50-50 Pozmix with 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Calculated top of cement - 6000'.

Second Stage: 125 sacks 65-35 Pozmix (12% Cement with 6-1/4 lbs. Gilsonite per sack, followed by 50 sacks Class "B" Neat Cement. Stage 3372'. Calculated top of cement - 2605'

FOR: DAVE M. THOMAS, JR.

18. I hereby certify that the foregoing is true and correct

SIGNED

ORIGINAL SIGNED BY

EWELL N. WALSH

Ewell N. Walsh, P.E.

TITLE

President, Walsh Engr.
& Prod. Corp.

DATE

3/5/80

(This space for Federal or State office use)

ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FEDERAL BUREAU OF
RECONSTRUCTION