

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
ODESSA NATURAL CORPORATION Attn: J. Strojek

3. ADDRESS OF OPERATOR
P.O. Box 3908 Odessa, Texas 79760

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1850'FSL, 790'FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE
Jicarilla Joint Venture

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jicarilla Joint Venture "KD"

9. WELL NO.

10

10. FIELD OR WILDCAT NAME
Chacon Dakota Associated Pool

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Section 3-T23N-R3W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

30-039-22151

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7228'GL, 7241'DF, 7242'KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/18/80 Spud Well

3/18/80 T.D. 275'. Ran 8 joints 8-5/8", 24.0 lb., K-55 casing (261.44') set at 276.44' with 275 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated approximately 2 barrels. Pressure test with 500 psig. Test ok.

4/1/80 T.D. 7640'. Ran 193 joints 4-1/2", 10.50 & 11.60, K-55 casing (7638.03') set at 7640.43' with:

First Stage: 510 sacks 50-50 Pozmix with 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Calculated top of cement - 5899'

Second Stage: 190 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite per sack followed by 50 sacks Class "B" Neat cement. Stage collar at 3347'. Calculated top of cement 2547'.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct.
FOR: ODESSA NATURAL CORPORATION President, Walsh Engr.

SIGNED: Ewell N. Walsh, P.E. & Prod. Corp. DATE: 4/8/80

(This space for Federal or State office use)

APPROVED BY: TITLE: DATE:

CONDITIONS OF APPROVAL, IF ANY:

COPIES FOR RECORD

NMOCC

APR 10 1980

*See Instructions on Reverse Side

BY: M. L. Kuchera

