DEPARTMENT OF THE INTERIOR (Other instructions on reverse side) UNITED STATES GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND MERIAL NO.

Do not	SUNDRY NOTICES AND REPORTS ON WELLS use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	Jicarilla Apache
. 🖼	GAS WELL OTHER	S PARM OR LEASE NAME

٠.			
	OIL GAS WELL OTHER	8. FARM OR LEASE NAME	
2.	NAME OF OPERATOR		
	ODESSA NATURAL CORPORATION Attn: John Strojek	Jicarilla Joint Venture "KD"	٠
		9. WELL NO.	
3.	ADDRESS OF CPERATOR	7	
	P.O. Box 3908 Odessa, Texas 79760	<u>'</u>	
_	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR WILDCAT	
1 .	See also space 17 below.)	Chacon Dakota Associated Poo	1د
	At surface	11. SEC., T., E., M., OR BLK. AND	
	850'FNL, 790'FEL	11 SEC., T., B., M., OR BLE. AND SURVEY OR AREA "Sec. 4-T23N-R3W	

18. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. N.M. 7131'GL, 7144'DF, 7145'KB

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data 16. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: REPAIRING WELL WATER SHUT-OFF PULL OR ALTER CASING TEST WATER SHUT-OFF ALTERING CASING PRACTURE TREATMENT MULTIPLE COMPLETE FRACTURE TREAT ABANDONMENT* SHOOTING OR ACIDIZING ABANDON* SHOOT OR ACIDIZE CHANGE PLANS (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) REPAIR WELL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.)* (Other)

Spud Well 10/5/79 10/6/79 T.D. 292'

Ran 8 joints 8-5/8", 24.0 lb., K-55 casing (273.36') set at 287' with 250 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement Circulated. Pressure test with 500 psig. Test ok.

10/20/79 T.D. 7560'.

Ran 193 joints 4-1/2", 10.50 & 11.60 1b. K-55 casing (1546.78') set at 7561' with:

First Stage:

510 sacks 50-50 Pozmix with 6-1/4 lbs. Gilsonite and

6 lbs. salt per sack.

Second Stage:

160 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite

per sack., followed by 50 sacks Class "B" Neat Cement

Stage collar at 3296'.

FOR: ODESSA NATURAL CORPORATION		
18. I hereby certify that the 10 PHOLD AL trace and torrect EWELL N. WALSH	President, Walsh Engineerin	ng 10/25/79
Ewell N. Walsh, P.E.	TITLE & Prod. Corp.	DATE
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE