

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
DAVE M. THOMAS, JR.

3. ADDRESS OF OPERATOR
P.O. Box 2026, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 800'FSL, 800'FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report required for multiple completion or zone change operations.)

U.S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

20101111

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/13/80
4/13/80 T.D. 260'. Ran 6 joints 8-5/8", 24.0 lb., K-55 casing, 242.23' set at 257.23' with 275 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated approximately 25 barrels. Pressure test with 500 psig. Test ok.

4/16/80 T.D. 7562'. Ran 187 joints 4-1/2", 10.50 & 11.60, K-55 casing, 7550.05' set at 7552.45' with:
First Stage: 440 sacks 50-50 Pozmix with 6-1/4 lb. Gilsonite and 6 lbs. salt per sack. Calculated top of cement 5850'.
Second Stage: 160 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite per sack, followed by 50 sacks Class "B" Neat cement. Stage Collar at 3297'. Calculated top of cement 2497'.

Subsurface Safety Valve: Manu. and Type _____ Ft.

18. I hereby certify that the foregoing is true and correct.

FOR: DAVE M. THOMAS, JR. President, Walsh Engr. & Prod. Corp.
SIGNED: Ewell N. Walsh DATE: 4/21/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
APR 23 1980
OIL CONSERVATION DIST. 3
APR 21 1980
FARMINGTON DISTRICT
BY: M. L. Richerson

NMOCC