

1 Stephen on  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

1 Crout  
SUBMIT IN TRIPPLICATE  
(Other instructions on the  
reverse side)

Field Approval  
Bureau Approval No. 42

SF-078272

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

BCO, Inc.

3. ADDRESS OF OPERATOR

135 Grant, Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1750' FSL 790' FEL Sec. 3 T23N R7W

RECEIVED

SEP 15 1981

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, AT, CR, etc.)

GR 6960

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

10. FIELD AND FORM OR WILDCAT

Undesignated Granero

Lybrook Gallup

11. SEC. T. R. M. OR BLM. AND

SURVEY OR TERRA

Sec. 3 T23N R7W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

RELL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of start  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones  
pertinent to this work.)

Intend to junk and abandon well. Well status as follows:

PBTD

= ~~6528~~ 6415'

Perfs Upper Graneros = 6309 to 6314

RBP

= 5750 Tested to 4000#'s

Perfs Gallup

= 5350 to 5588 (15 selective holes)

RBP

= 5300 Tested to 3000#'s

Retrievamatic Packer = 5290 with tubing cut off at 5245

Washed over fish from 5245 to 5290. Caught fish with overshot and couldn't  
pull packer. Pulled overshot off fish and came out of hole.

Determined well has hole in casing from 5040 - 5200. Have another hole from  
4127 - 4158. Intend to plug well as follows:

Run tubing in to fish at 5245. Spot 50 sacks of cement. Pull tubing  
to 4350, shut rams on BOP and pump 4 bbls. down tubing which should  
put cement on outside of hole.

Spot cement plugs as follows:

4077 - 4208

3430 - 3530

2393 - 2493

1970 - 2070

1552 - 1662

1322 - 1422

0 - 50

Put Dryhole marker in surface.

The above program was verbally approved by Mr. Richard Bell on 9-14-81.  
He was also advised plugging would be done 9-15-81.

The above program was verbally explained to Mr. Frank Chavez with the OCC  
in Aztec on 9-14-81 and he concurred with the program.

APPROVED

SEP 22 1981  
Duan Elliott  
For JAMES F. SIMS  
DISTRICT OIL & GAS SUPERVISOR

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry R. Blythe

TITLE

President

DATE 9-14-81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOCC