

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR

Reading & Bates Petroleum Co.

3. ADDRESS OF OPERATOR

1125 17th Street/Suite 2300 Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1830' FSL, 1840' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other)

5. LEASE

#156

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Lindrith 2

9. WELL NO.

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 2, T 23N, R 2W

12. COUNTY OR PARISH

13. STATE

Rio Arriba

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7346' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

To plug subject well we propose to set plugs over the following intervals:

Dakota Top @ 7512' cmt from 7429'-7529' 35 sx  
Gallup Top @ 6426' cmt from 6334'-6434' 35 sx  
Mesa Verde Top @ 4856' cmt from 4769'-4869' 35 sx  
Picture Cliffs Top @ 3106' cmt from 3017'-3117' 35 sx  
Ojo Alamo Top @ 2612' cmt from 2517'-2617' 35 sx  
Surface csg @ 375' cmt from 140' - 425' 100 sx  
Surface plug from 25' to surface 10 sx w/ dry hole marker

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David L. Blosser TITLE Petroleum Engineer DATE 12/15/80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

APPROVED

DEC 18 1980  
JAMES F. SIMS  
DISTRICT OIL & GAS SUPERVISOR