

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR DAVE M. THOMAS, JR.	8. FARM OR LEASE NAME Amerada Jicarilla
3. ADDRESS OF OPERATOR P. O. Box 2026 Farmington, N.M. 87401	9. WELL NO. 3
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 880'FNL, 990'FWL	10. FIELD AND POOL, OR WILDCAT Chacon Dakota Assoc.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 2-T23N-R3W N.M.P.M.	12. COUNTY OR PARISH Rio Arriba
14. PERMIT NO.	13. STATE N.M.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7165'GL, 7178'DF, 7179'KB	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/5/81 T.D. 7634' Ran 242 joints 4-1/2", 10.50 & 11.60, K-55 casing (7611.95) set at 7612.35' with:

First Stage: 510 sacks 50-50 Pozmix and 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Calculated top of cement 5875'.

Second Stage: 160 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite per sack, followed by 50 sacks Class "B" Neat Cement. Stage Collar at 3375'. Calculated top of cement 2575'.

ACCEPTED FOR RECORD

MAR 11 1981

FARMINGTON DISTRICT

FOR: DAVE M. THOMAS, JR.

BY

18. I hereby certify that the foregoing is true and correct

President, Walsh Engr. & Production Corp.

SIGNED

EWELL N. WALSH, P.E.

TITLE

DATE 3/6/81

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side