Constitution of the Section Section Section

問題 The Application of the Other Control

5. LEASE NM-23049

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| GEOLOGICAL SURVEY   | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME None  |
|---|--|
| THE PEROPE ON WELLS   | 7. UNIT AGREEMENT NAME   |
| SUNDRY NOTICES AND REPORTS ON WELLS   | West Lybrook Unit  |
| Oc not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)  | 8. FARM OR LEASE NAME  |
| 1 all 11 G26 C  | Federal - 6  |
| 1. oil gas other well other   | 9. WELL NO.  |
| 2. NAME OF OPERATOR   | #43  10. FIELD OR WILDCAT NAME   |
| Kenai Oil and Gas Inc.  | Lybrook Gallup Ext.  |
| 3. ADDRESS OF OPERATOR<br>717 17th St., Ste. 2000, Denver, CO 80202-3373  | 11. SEC., T., R., M., OR BLK. AND SURVEY OR  |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17  | AREA   |
|   | Sec. 6, T23N-R7W   |
| AT SURFACE: 2040' FSL - 340' FEL  | 12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico   |
| AT TOP PROD. INTERVAL: AT TOTAL DEPTH:  | 14. API NO.  |
|   | 14. AFT NO.  |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,<br>REPORT, OR OTHER DATA  | 15. ELEVATIONS (SHOW DF, KDB, AND WD)  |
|   | 7007' GL; 7021'KB  |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  |  |
| TEST WATER SHUT-OFF   |  |
| FRACTURE TREAT  SHOOT OR ACIDIZE  |  |
| REPAIR WELL   | (NOTE: Report results of multiple completion or zone change on Form 9-330.)  |
| PULL OR ALTER CASING  | change on Form 5-330.)   |
| MULTIPLE COMPLETE   | , tautiway   |
| ARANDON*  | N. M.  |
| (other) Well Status   | Company of the Astronomy of the Astronom |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine TD 5802' (loggers). Ran 139 jts, 5½", 15.5#, Cemented 1st Stage with 625 sxs Class B 50/50 10% salt. Circ 2½ hrs between stages. Cement B 65/35 Poz with 6% gel, 1/4# cellflake, 2% Ca 65/35 Class B Poz with 2% gel, .6% D60 flac and 10:15 p.m., 8/21/81. Float held ok. Circulat Present operation: waiting on completion unit | J55 casing and set @ 5792.67'KB. Poz with 2% gel, .8% D60 and sed 2nd Stage with 450 sxs Class aCl and tailed in with 100 sxs ad 10% salt. Bumped plug @ sed 50 bbls of cement to surface.  SEP & = 1981   |
| Subsurface Safety Valve: Manu. and Type   | OIL CON. COM.  |
| 18. Thereby certify that the foregoing is true and correct  Manager - Drill   | ling &   |
| SIGNED ESTER B. Jude TITLE Production   | DATE 8/25/81   |
| (This space for Federal or State  | office use)  |
| TITLE   | OAPETER  |
| APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:   |  |
|   | 1981   |
| NMOCC   |  |
|   | era.   |
| *See Instructions on Revers   | BYSmm  |
|   |  |