

5 USGS, Fmn 1 McHugh

1 So Un Expl.

1 File 1 TR

Form Approved  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
DUGAN PRODUCTION CORP.
3. ADDRESS OF OPERATOR  
P O Box 202, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)  
AT SURFACE: 880' FNL - 800' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON ☐  
(other) ☐


SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

XX 2-7/8" csg. & cement

5. LEASE  
NM 28738
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Adare
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Ballard P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 12 T23N R6W
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6760' GL

(NOTE: Report results of multiple completions on one change on Form 9-331.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-19-81 TD 2200' - T.I.H. with "side door". Wash over shoe. Knocked logging tool loose. Recov; red logging tool. T.I.H. Drilled to 2200'. Laid down drill pipe. Rigged up and ran 76 jts. 2-7/8" OD, 6.4#, 10RD, NEUE, L.S. tbgs. for csg. T.E. 2197.92' set at 2196' GL.

Cemented with 75 sx 2% lodense followed by 50 sx class "B" neat. Total cement slurry 216.5 cu.ft. Good circulation throughout job. (Estimated cement top 300') P.O.B. at 12:00 midnight.  
11-18-81.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist

DATE 11-20-81

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY.

TITLE DATE