## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5	LEASE
	\n m 080273
6	. IF INDIAN, ALLOTTEE OR TRIBE NAME
7	. UNIT AGREEMENT NAME
8	. FARM OR LEASE NAME
	Hanson Federal
9	). WELL NO.
10	. FIELD OR WILDCAT NAME
	Lybrook Gallup
11	SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	Sec. 3, T23N, R7W
12	R. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico
14	I. API NO.
1!	5. ELEVATIONS (SHOW DF, KDB, AND WD)
	7044 GR 7056 KB
<del>-   </del> -	NOTE: Report results of multiple completion or zone change on Form 9–330.)
* <u>:</u> .	
SU:	(UEY) 4.
all	pertinent details, and give pertinent dates,

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331-C for such proposals.) gas well X other well 2. NAME OF OPERATOR Byron Oil Industries, Inc. 3. ADDRESS OF OPERATOR 80234 2200 E. 104th Ave, Suite 217, Thornton, Co. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 686' FSL, 1806' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL **PULL OR ALTER CASING** MULTIPLE COMPLETE **CHANGE ZONES** ABANDON\* s. glouddida (other) <u>Drilling</u> FARIAING (ON, 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly star

including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well was spudded 1-4-82. 8 5/8" surface casing was set at 268' KB with cement circulated to surface. 7 7/8" hole was drilled to 5801 with 4½" 10.5# ST&C casing set at 5801' KB. Sufficient cement was used to cement casing to surface. A DV tool was set at 4574' KB. No cement was circulated out on either stage. When the completion rig is moved in, a cement bond log will be run to determine cement top. The casing was set on 1-15-82.

Subsurface Safety Valve: Manu. and Type Set @ 18. I hereby certify that the foregoing is true and correct Petroleum EngineerATE SIGNED (This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: DATE

ACCEPTED FOR RECORD

FEB 1 1982

\*See Instructions on Reverse Side

TITLE

