

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR
Robert L. Bayless3. ADDRESS OF OPERATOR
P.O. Box 1541, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1800' FSL & 1790' FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Changeout tubing

SUBSEQUENT REPORT OF

RECEIVED
MAR 17 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.5. LEASE
Contract 776. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
AXI A9. WELL NO.
1110. FIELD OR WILDCAT NAME
Ballard Pic. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15, T23N, R5W

12. COUNTY OR PARISH
Rio Arriba13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6741' KB, 6733' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-11-83 Rig up Bayless Rig #4. Blowdown well, nipple down wellhead assembly.
Tripped 1-1/4", 2.4#/ft., EUE tubing out of hole. Tripped in hole
with 3/4", 1.2#/ft., J-55, 10rd, EUE tubing and landed as follows:

| Description | Length | Depth |
|------------------------------|---------|---------|
| KB to landing point | 8.00 | 0-8 |
| 1 jt. 1-1/4", 2.4#/ft. tbg. | 32.70 | 8-40 |
| 1 ea. 1-1/4"x3/4" changeover | .50 | 40-41 |
| 71 jts. 3/4", 1.2#/ft. tbg. | 2099.63 | 41-2141 |

Nippled up wellhead assembly; released rig.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kevin A. McGowan TITLE Engineer DATE March 16, 1983

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAR 18 1983

*See Instructions on Reverse Side

NMOCC