

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Chace Oil Company, Inc.
3. ADDRESS OF OPERATOR
313 Washington, S. E., Albuquerque, NM 87108
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
Unit "I" 2310' FSL & 990' FEL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other)

Progress Report

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-11-82 Ran 174 joints of 11.6# 4 1/2" casing. Shoe set at 7543'. 43.73' shoe joints. Float collar at 7499'. Short joints at 6128' to 6149'. D. V. Tool at 3281' to 3284'. Cement basket at 7155', 6456', 6193', 3368' and 2542'. Circulated 25 minutes. Pumped 1,000 gallons of mud flush. Cemented with 730 sxs of 50/50 posmix. 2% gel, 6 1/4# gilsonite, 6# salt per sack. Plugged down at 3:00 A. M., June 11, 1982. Lost circulation with 80 barrels of displacement in top of cement approximately 3400'. Second stage. Opened D. V. Tool, and circulated 3 hours. Pumped 1,000 gallons of mud flush. Cemented with 405 sxs of 65/35 posmix. 12% gel, 6 1/4# gilsonite per sack, followed by 50 sxs of Class B neat. Plugged down at 7:14 A. M., 6/11/82. Circulated 12 barrels of cement to surface. Release rig.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

President

DATE

June 11, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 15 1982

*See Instructions on Reverse Side

NMOCC

FARMINGTON DISTRICT
BY SAS