

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
Getty Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 3360, Casper, WY 82602-3360

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1510' FNL & 1730' FEL of Sec. 5
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) SRA - Dakota Zone only

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

Contract #44 - Tract #91

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

-

8. FARM OR LEASE NAME

Jicarilla "D"

9. WELL NO.

#3

10. FIELD OR WILDCAT NAME

Lindrith Gallup-Dakota South

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

G, Section 5-T23N-R4W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

-

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7040' Graded GR

RECEIVED

(NOTE: Report results of multiple completion or change on Form 9-330.)

SEP 15 1983

OIL CON. DIV.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 8-29-83, Mr. Mark Kramer w/ Getty received verbal from Mr. Ken Townsend as follows
On 8-30-83, MIRU pulling unit. TOH w/rods & pump. TIH w/ tbg & tagged bridge plug @ 7050'. TOH w/bridge plug & tbg. TIH w/ 5 1/2" CIBP on wireline. Set CIBP @ 7090' KB. Dumped 50' cement on top of CIBP.

On 8-31-83 RIH w/ 2 3/8" production tubing as follows: bottom of tubing 6993'-6962', perforated sub 6962'-6959', SN @ 6959'-6958' & tbg anchor @ 6958'-6955'. Set tbg anchor. Ran 2" x 1 1/4" x 84' pump and rods. Hung well on. Began production 8-31-83 (8 SPM x 64" SL).

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Area

SIGNED

[Signature]

TITLE Superintendent

DATE

9-8-83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 13 1983