5. LEASE

Tribal Contract #47

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas Other	Jicarilla Tribal #47
	9. WELL NO. #3-49-3V
2. NAME OF OPERATOR Chace Oil Company, Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	S. Lindrith Gallup Dakota
313 Washington, SE, Albuquerque, NM 87108	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA -
below.) AT SURFACE: Unit "C", 336 FNL & 2310 FWL	Sec. 11, T23N,R4W
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH   13. STATE   Rio Arriba   New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	7293' GR 7307' KB
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF  FRACTURE TREAT	
FRACTURE TREAT	
TEST WATER SHUT-OFF  FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL	CHATE: Report results of multiple completion or zone change on Form 9–330.)
PULL OR ALTER CASING []	change on Form 9-330.)
MULTIPLE COMPLETE	
7	
(other) Progress Report	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent.)	lirectionally drilled, give subsurface locations and
725/83: Ran 194 joints of 4½" 11.6# N-80 casing. Shown 7589'. Short joint 6114' to 6134'. D. V. Too @ 7393', 7157', 6723', 5088', 4537', 3001', 20	ol @ 3237'. Cement baskets
With casing at bottom, circulated hole 1/2 hor Cemented 1st stage with 800 sacks, (1440 CF) Gilsonite, and 6#/sk salt. Plug down @ 5:00 1	50/50 pozmix, 2% gel, 6¼#/sk
Opened D. V. Tool. Circulated 3 hours. Second flush. Cemented with 400 (720 CF) sacks 65/39 Gilsonite. Tailed in with 50 (90 CF) Class B	5 Pozmix, 12% gel, 6½#/sk
Circulated 3 bbls. cement to surface.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foresting of true and correct	
SIGNED . Myller TITLE President	January 26, 1983
(This space for Federal or State off	fice use)
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	
REGEIVEM	andre fem fine fille film en
See Instructions on Reverse :	Side (FER 9.000)

FARMINGTON DISTRICT