5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

DEPARTMENT OF THE INTERIOR	Tribal Contract #47
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
The past use this form for proposals to drill or to deepen or plug back to a different	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME -
1. oil 🖂 gas 🗇	Jicarilla Tribal #47
well well other	9. WELL NO.
2. NAME OF OPERATOR	#4 *** V
Chace Oil Company, Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	S. Lindrith, Gallup Dakota
313 Washington, SE, Albuquerque, NM 87108	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) Unit 'E' - 460' FWL & 1750' FNL AT SURFACE:	Sec. 11, T23N,R4W
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE - New Mexico
AT TOTAL DEPTH:	Rio Arriba New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	# 1
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	7372' GR 7386' KB
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF FC	
FRACTURE TREAT	IDECEIVEM
REPAIR WELL	(NO)E: Report results of multiple completion
PULL OR ALTER CASING 🔲	chinds on Form 9-330.)
MULTIPLE COMPLETE	YEY, JUNEAU THE S
CHANGE ZONES ABANDON* GARMINGTON, N. M.	OIL CON. DIV.
(other)	
AT A SOCIAL PROPERTY OF COMPLETED OPERATIONS (S)	- CEST. 3 FE
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di 	irectionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertinen	t to this work.)*
•	
See Well History attached. Day #5 through Day #8.	
	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
	프로그 등 등 중심 중심 하는 중심 하다 하는 중심 하다 하는 것이 없는 것이 되었다.
	발표되는 경우 학원의 기
	그 그 그 그 그 그 중위장 취임 통일 이 활동하다.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED . W Illu , TITLE President	DATE June 10, 1983
(This space for Federal or State office use)	
·	• - ^ ^ 토리집하지 않는 불림하였다.
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
	Table Control of the
South four for record	Control of the contro
	실패하다 그 병기 출혈호
*See Instructions on Payerse S	Side

JUN 16 1682



RECEIVED

Page Three

6/7/83:

OIL CON. DIV.

Day #5. Present operation: drilling. Depth today: 4529'. Made 641' last 24 hours. Formation: sand and shale. Rotary RPM: 65. Weight on bit: 35,000#. Present drilling rate: 23 ft/hr. Pump - liner size: 5½. Pressure: 1,000#. 58 strokes per minute. Mud vis: 35. Wt.: 9.2. W. L.: 7.6. Mud additives last 24 hours: 27 gel, 1 1/2 soda ash, 3 thinner, 1 caustic soda, 1 preservative, 3 LCM, 40 barrels of oil. Deviation record: 1/2° @ 4099'. Bit #4: 7 7/8", J22; 955', 36 1/4 hours. 1/4 hour Rig service

1/4 hour Rig service
1/2 hour Survey
23 1/4 hours Drilling

6/8/83:

Day #6. Present operation: drilling. Depth today: 5149'. 24 hour footage: 620'. Formation: sand and shale. Rotary RPM: 65. Weight on bit: 38,000#. Present drilling rate: 22 ft/hr. Mud vis: 36. Wt.: 9.2. W. L.: 9.3. Mud additives last 24 hours: 48 gel, 3 soda ash, 3 thinner, 1 caustic soda, 20 barrels oil. 1/2°@ 4589'; 1/2°@ 5145'. Bit #4: 7 7/8", J22; 1675', 59 1/4 hours.
1 hour - RS and Surveys
23 hours - Drilling

6/9/83:

Day #7. Present operation: drilling. Depth today: 5530'. 24 hour footage: 381'. Formation: sand and shale. Rotary RPM: 60. Weight on bit: 40,000#. Present drilling rate: 22'/hr. Pump - liner size: 5½. Pressure: 1,000#. 58 strokes per minute. Mud vis: 42. Wt.: 9.3. W. L.: 7.8. Mud additives last 24 hours: 42 gel, 1 soda ash, 1 caustic soda, 1 preservative, 2 thinner, 6 starch, 40 barrels of oil. Deviation record: 3/4° @ 5482'. Bit #4: 7 7/8", J22; 1908', 73 1/2 hours. Bit #5: 7 7/8", F2; 48', 2 hours.

1 1/2 hours

Rig
6 1/4 hours

Trip for bit

6/10/83:

16 1/4 hours

Day #8. Present operation: drilling. Depth today: 6005'. 24 hour footage: 475'. Formation: sand and shale. Rotary RPM: 60. Weight on bit: 40,000#. Present drilling rate: 18 ft/hr. Mud vis: 41. Wt.: 9.5. W. L.: 7.3. Mud additives last 24 hours: 42 gel, 1 1/2 soda ash, 1 caustic soda, 6 thinner, 20 barrels of oil. Bit #5: 7 7/8", F2; 125', 25 1/4 hours.

Drilling

23 1/4 hours Drilling
1/4 hour Rig Service

1/2 hour Survey (No deviation record available)