

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other ☒ Commingled
2. NAME OF OPERATOR
W. B. Martin & Associates
3. ADDRESS OF OPERATOR
2110 North Sullivan, Farmington NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL and 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Production Casing & Cement

SUBSEQUENT REPORT OF:

RECEIVED
MAY 4 1983
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
Contract #362
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
9. WELL NO.
#11 Martin-Florance
10. FIELD OR WILDCAT NAME
South Lindrith Gallup Dakota Ext.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NE/4 SW/4 Sec 5
T23N R4W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
Cr. 6971'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completed Operations: 04/30/83 Reached T. D. 7200'

05/02/83 Ran 7186' of new K-55 5½" 17 lb/ft casing

Cemented as follows:

Equipment Depth Cement

Guide Shoe 7186'

Float Collar 7150' 600 sks (966ft³) 65/35 Poz 6% gel 6½# Kolite 10% Salt
Tail in 500 sks (660ft³) 65/35 Poz 2% gel 6½# Kolite 10% SaltD. V. Tool 2298' 300 sks (483ft³) 65/35 Poz 6% gel 6½" Kolite 10% Salt

Current Operations: Waiting on Cement

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. B. Martin TITLE Operator DATE May 6, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 17 1983

*See Instructions on Reverse Side

FARMINGTON DISTRICT
BY SK

NMOCC