

Distribution: O+4 (BLM); 1-Well File; 1-Crystal; 1-Earleen

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir

Use "APPLICATION FOR PERMIT-" for such proposals

93 JUN 30 AM 10:30
070 FARMINGTON, NM

Designation and Serial No.
NM-23738

If Indian, Allottee or Tribe Name

If Unit or CA, Agreement Designation

Well Name and No.

Margarita No. 1

API Well No.

30-039-23194

Field and Pool, or Exploratory Area

Counselors Gallup-Dakota

County or Parish, State

Rio Arriba, New Mexico

12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6/2/93 MIRU A-Plus Service.

6/3/93 Bleed well down. Pumped 25 bbls water to kill well. Unseat pump. Start pulling rods.

6/4/93 Pump 45 bbls hot water down casing. LD rods, pump 25 bbls water down tubing. ND WH, NU BOP. TOOH with 5624' of 2-3/8" tbg. TIH to 5690'. Spot #1 plug from 5624'-4966' with 50 sxs "B" neat cement. Pull above cement, spot 20 bbls (8.5#) mud from 5000' to 3693'. TOOH. WOC.

6/7/93 Tag Plug #1 @ 4960'. Pull tubing to 3648'. Plug #2 from 3648' to 2990' with 50 sxs "B" neat cement. Spot 30 bbls (8.5#) mud from 2990' to 2145'. Pull tubing to 2136'. Plug #3 from 2136' to 1334' with 61 sxs "B" neat cement. Spot 17 bbls (8.5#) mud from 1334' to 263'. LD tubing. Plug #4 from 263' to surface with 21 sxs "B" neat cement. ND BOP. Cut off wellhead. Install P&A marker. RDMOL on 6/7/93. Rehabilitation to follow ASAP.
Note: All cement "B" neat, yield 1.15 cu.ft./sx, density 15.6#/gal.)

14. I hereby certify that the foregoing is true and correct

Signed

Steven S. Dunn

Title Operations Manager

Date

6/29/93

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD