5. LEASE

Tribal Contract #47

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

0.0000000000000000000000000000000000000	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
	Jicarilla Tribal Contract #47
1. oil XX gas	9. WELL NO.
2. NAME OF OPERATOR	AS-5-AS
	10. FIELD OR WILDCAT NAME
Chace Oil Company, Inc. 3. ADDRESS OF OPERATOR	South Lindrith Gallup Dakota
313 Washington, SE, Albuquerque, NM 87108	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) Unit 'F' - 1890' FNL & 1900' FWL	Section 11, T23N, R4W
AT SURFACE:	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	7
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 7422' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	mile in the
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Reppin results of multiple completion or zone enable on Form 9-330.)
702 01 72 21 01 01 01	1 V change on Form 9-330.)
MULTIPLE COMPLETE SEP 1	9 1983 OF THE STATE OF
CHANGE ZOIVES	
(other) run casing (amended 9/14/83 Rungers)	ND MANAGEMENT
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertined	ditectionally divised, give appaulace locations and
Ran 194 joints plus a short joint of 41/2",	11 6 lb/ft N-80 casing
set at 7671 KB. Guide Shoe at 7670. Flo	
joint from 6025-6052. D.V. tool at 3221.	
6921, 6290, 5985, 5315, 2630. 1st stage;	
21. Cemented first stage with 1250 sxs.	
2% gel, 6¼ lb/sk Gilsonite, 6 lb/sk salt.	
Opened D.V. tool. Circulated upper stage	
pumped 20 bbls. mud flush. Cememted 2nd	
65/35 pozmix, 12% gel, 6¼ lb/sk Gilsonite	
(59 CF) Class B neat. Plug down at 10:41	
3 bbls. cement to surface.	
	HE HERE HERE HERE HERE HERE HERE HERE H
Subsurface Safety Valve: Manu. and Type	Ft.
18. I hereby certify that the foregoing is true and correct	
	September 16 1983
(This spice for Federal or State of	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
CONDITIONS OF AFFROYAL II AND	ACCEPŢĘD, FORĘ ŔECORD
•See Instructions on Reverse	SEP 3 0 1983
See meatingious on keekise	
	FARMING FOR MESOURCE AREA

BY Jnn