

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved:
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR

P.O. Box 1290, Farmington, New Mexico 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface 1768' FSL; 2235' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether to top of hole, etc.)

7242'

5. LEASE DESIGNATION AND SERIAL NO.

SF-078272 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dunn

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Lybrook Gallup/Undes. Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 9, T23N-R7W NMPM

12. COUNTY OR PARISH 13. STATE

Rio Arriba New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Verbal approval from John Keller and Errol Beecher for program to plug and abandon present new hole on 1-12-84 with program as follows:

Cement plug 50' above and below Ojo Alamo

Cement plug 50' above and below kick out point w/50% excess cement.

Cement plug 50' above and below surface casing shoe w/50% excess cement.

Cement plug at surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. A. Edmister

TITLE

Engineering Analyst

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

RECEIVED
FEB 14 1984

OIL CON. DIV.
DIST. 3

APPROVED
DATE February 7, 1984

DATE FEB 13 1984

AREA MANAGER
FARMINGTON RESOURCE AREA