

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
DUGAN PRODUCTION CORP.
3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 980' FNL - 810' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☐

XX Spud and Surface casing

5. LEASE
NM 24458
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Fahrenheit
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Counselors Gallup *Liketa*
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 11, T23N, R6W, NMPM
12. COUNTY OR PARISH
Rio Arriba
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6815' GL; 6827' RKB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-27-84 Moved in and rigged up Four Corners Drilling Co. Rig #5. Spudded 12 1/4" hole at 10:45 a.m. 5-26-84. Drilled to 210'. Ran 7 jts. 8-5/8" O.D., 24#, 8 Rd, ST&C casing. T.E. 197' set at 208' RKB. Cemented with 135 sx class "B" plus 2% CaCl (159 cf). Circulated approx. 2 bbls. cement to surface. P.O.B. at 2:15 p.m. 5-26-84. W.O. cement 12 hrs. (Pressure tested surface casing and B.O.P. to 600 psi for 30 min. Held OK.)

RECEIVED

JUN 04 1984

OIL CON. DIV.

DISC. 3 Ft.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 5-29-84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 01 1984

FARMINGTON RESOURCE AREA

RV 5mm