

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ Co-mingled2. NAME OF OPERATOR
W.B. Martin & Associates, Inc.3. ADDRESS OF OPERATOR
2110 N. Sullivan, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 770' FNL and 900' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) Case and Cement Intermediate

5. LEASE

Contract #398

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

#31 Martin-Whittaker

10. FIELD OR WILDCAT NAME

~~Wildcat~~ S. Genduth Galkin

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

NENE Sec. 16

T23N R4W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completed Operations 5/24/84 Drilled 8 3/4" hole to 5227' K.B. with low solids, low water loss mud. Ran 5250' of new J-55 26#/ft 7" casing. Guide Shoe @ 5225' K.B. fill collar @ 5185' K.B. Cemented with 304ft³ (200sxs) 50/50 poz plus 6% gell plus 5#/sx Hiseal plus 10% Salt and 1% CaCl₂. Tail in with 420.50ft³ (290sxs) of Class B + 10% Thixaid + 1% CaCl₂. Cement height is 1400'.

Proposed Operation: WOC 12hrs.

R

JUN 08 1984

Subsurface Safety Valve: Manu. and Type

OIL CON. DIV.

DIST. 3

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

W.B. Martin

TITLE

Operator

DATE

5/29/84

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 07 1984

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY

Smm

NMOCC