

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Bolack Minerals Co.

3. ADDRESS OF OPERATOR
P.O. Box 255, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 2040' fsl, 810' fel
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)		Spud	<input checked="" type="checkbox"/>

5. LEASE
NM-067612

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A

7. UNIT AGREEMENT NAME
N/A

8. FARM OR LEASE NAME
Bolack "E"

9. WELL NO.
4-R

10. FIELD OR WILDCAT NAME
Clerg Pict. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 1, T23N-R6W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
N.M.

14. API NO.
30-039-70228-83

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6747 Gr., 6753' Est. KDB

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 08 1984

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well at 11:45 a.m., May 7, 1984
Drilled 9 7/8" hole to 105 ft. Ran 3 joints 7", 26 lb., K-55, ST&C casing to 100 ft. and cemented with 59 cu. ft. Class B cement with 4% calc. chloride, 1/4 lb/sk. flocele flakes. Circulated 3.0 bbls. cement slurry to surface. Plug down at 7:15 p.m., 5/7. Will wait on cement to set 12 hrs. and drill out with 6 1/2" bit.

RECEIVED

MAY 14 1984

OIL CON. DIV.
DIST. 3

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. Speer TITLE Agent DATE May 8, 1984

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: