

UN. D STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well2. NAME OF OPERATOR  
Chace Oil Company, Inc.3. ADDRESS OF OPERATOR  
313 Washington, SE, Albuquerque, NM 871084. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Unit 'O' - 660' FSL & 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

☐ TEST WATER SHUT-OFF  
☐ FRACTURE TREAT  
☐ SHOOT OR ACIDIZE  
☐ REPAIR WELL  
☐ PULL OR ALTER CASING  
☐ MULTIPLE COMPLETE  
☐ CHANGE ZONES  
☐ ABANDON\*  
(other)

## SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA5. LEASE  
Jicarilla Tribal Contract #71  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla Apache  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Jicarilla Contract #71  
9. WELL NO.  
70-39  
10. FIELD OR WILDCAT NAME  
South Lindrith-Gallup Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 9, T23N, R4W  
12. COUNTY OR PARISH  
Rio Arriba  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7101' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded at 12:00 midnight on 10/23/84 with Arapahoe Drilling Company rig #11. Ran 5 joints of 8 5/8", 24#, J-55, 211' set at 224' KB. Cemented with 170 sks (200 CF) Class B neat, 1/4 lb/sk Flocele, 3% calcium chloride. Plug down at 5:30 A. M. on 10/23/84. Circulated 5 bbls. cement to surface.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

President

DATE

October 24, 1984

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NOV 15 1984

\*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

OPERATOR

BY