

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	5. LEASE DESIGNATION AND SERIAL NO. Contract 398
2. NAME OF OPERATOR Robert L. Bayless	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla
3. ADDRESS OF OPERATOR P.O. Box 168, Farmington, NM 87499	7. UNIT AGREEMENT NAME Jicarilla 398 B
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 560' FSL & 890' FWL	8. FARM OR LEASE NAME Jicarilla 398 B
14. PERMIT NO.	9. WELL NO. #1
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 7030' G.L.	10. FIELD AND POOL, OR WILDCAT Ballard Pic. Cliffs
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 16, T23N, R4W
	12. COUNTY OR PARISH 13. STATE Rio Arriba NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Spud & set surf. csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

DAILY REPORT

- 4-20-85 Spud well at 6:00 p.m. 4/19/85. Drilled 130 ft. of 9-7/8" hole. Ran 122 ft. of 7" 23#/ft J-55 used casing. Landed @ 120' RKB. Cemented surface casing with 47 ft<sup>3</sup> Class B cement with 2% CaCl<sub>2</sub>. Good circulation throughout job. Circulated cement to surface. Plug down at 11:15 p.m. 4-19-85. WOC 10 hours.
- 4-21-85 Drilling @ 1340'. Mud wt 8.9; Visc. 30; W.L. 8.0; Deviation 1/4° @ 540', 1/2° @ 1260'.
- 4-22-85 Tripping @ 2181'. Mud wt 8.9; Visc. 30; W.L. 9.0. Deviations 1-3/4° @ 2181', 1 1/2° @ 1860'.

APR 29 1985

U.S. GEO. SURV. DIV.  
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

*Kenn H. McLow*

TITLE Petroleum Engineer

DATE April 22, 1985

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NMOCC