

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use form 9-331-C for such purposes.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

JACK A. COLE

3. ADDRESS OF OPERATOR

P. O. BOX 191, FARMINGTON, N.M. 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1740' FNL 720' FWL

AT TOP PROD. INTERVAL: SAME

AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☒

☐

☐

☐

☐

☐

☐

☐

RECEIVED

MAY 08 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-3-85 SPUD 10:00 P.M. RAN 6 JTS 8-5/8", 24.0 LB. ERW, 248.05, SET AT 260.05. CEMENTED WITH 250 SACKS (295 CU. FT.) CLASS "B", 3% CACL AND 1/4 FLOCELE PER SACK. PLUG DOWN 8:00 A.M. 5-4-85 CIRCULATED CEMENT TO SURFACE. PRESSURE TEST CASING TO 500 PSI. TEST OK.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED DeWayne Blawie TITLE PROD. SUPT. DATE MAY 6, 1985

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 08 1985

*See Instructions on Reverse Side

NMOCQ

FARMINGTON RESOURCE AREA
DV E J