

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

BANNON ENERGY INCORPORATED

3. Address and Telephone No.

3934 FM 1960 WEST, SUITE 240, HOUSTON, TX 77068 (713) 537-9000

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

655' FNL, 945' FEL
Sec. 1-T23N-R7W

5. Lease Designation and Serial No.

SF-078362

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Marcus No. 6

9. API Well No.

30-039-23692

10. Field and Pool, or Exploratory Area

Lybrook-Gallup

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

See Attached for Plugging Summary

RECEIVED
APR 14 1993
OIL CON. DIV
DIST. 3

RECEIVED
BLM
93 MAR 31 AM 11:17
070 PLUGGING DIV, NM

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Dwayne Blanchett

Title Field Foreman

Date 3-26-93

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

APPROVED

APR 12 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

DISTRICT MANAGER

*See Instruction on Reverse Side

NMOCD

March 15, 1993

Bannon Energy

Marcus #6

NE, NE, Sec. 1, T23S, R7W

Rio Arriba County, NM.

SF-078362

PLUG AND ABANDONMENT REPORT

Cementing Summary:

Plug #1 from 5513' to 4815' with 53 sxs Class B cement.

Plug #2 from 3535' to 3435' with 54 sxs Class B cement, squeezed 49 sxs under CR and spot 5 sxs above.

Plug #3 from 2029' to 909' with 85 sxs Class B cement.

Plug #4 from 318' to surface with 129 sxs Class B cement, circulate good cement to surface.

Plugging Summary:

3-11-93 Drive rig and equipment to location. Rig up and spot equipment; lay relief line to pit. Open well up, ND wellhead; NU BOP and test. POH with 167 joints 2-3/8" tubing, 5450'; wet string, recovered stop and piston. Cleaned up work area. RIH with open ended tubing to 5513'. Pump 20 bbls water down tubing. Plug #1 from 5513' to 4815' with 53 sxs Class B cement. POH to 3912'. Shut in well and SDFN.

3-12-93 RIH with tubing and tag cement at 4996'. Mix and spot 22 bbls 9# 50 vis mud from 4996' to 3535'. POH with tubing. Perforate 2 holes at 3535'. PU 4-1/2" cement retainer and RIH; set at 3401'; pressure test tubing to 1500#; pump into holes. Plug #2 from 3535' to 3435' with 54 sxs Class B cement, squeezed 49 sxs under CR and spot 5 sxs above. POH to 3272'. Mix and spot 20 bbls 9# 50 vis mud from 3272' to 2001'. POH to 2029'. Plug #3 from 2029' to 909' with 85 sxs Class B cement. POH to 901'. Mix and spot 11 bbls 9# mud from 901' to 300'. POH and LD tubing. Perforate 2 holes at 318'. Establish circulation out bradenhead. Plug #4 from 318' to surface with 129 sxs Class B cement, circulate good cement to surface. Shut in well and WOC. Open well up and ND BOP. Cut off wellhead and install P&A marker with 10 sxs cement. Rig down and move off location.