

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
JACK A. COLE

3. ADDRESS OF OPERATOR
P. O. BOX 191, FARMINGTON, N.M. 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1830' FSL, 880' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JUN 13 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/24/85 - SPUD 12-1/4 SURFACE HOLE 6:00 P.M.

5-25-85 - RAN 19 JTS., 8-5/8", 24.0 LB. ERW CASING, 777.38' SET AT 789.38'.
CEMENTED WITH 500 SACKS (590 CU.FT.), CLASS "B", 3% CACL AND
1/4 LB. FLOCELE PER SACK. PLUG DOWN 4:25 P.M. CIRCULATED 50
BBLs. CEMENT

5/26/85 PRESSURE TEST CASING WITH 500 PSI FOR 15 MINUTES. TEST OK.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dwayne Blissett TITLE PROD. SUPT. DATE JUNE 3, 1985

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

JUN 14 1985

FARMINGTON RESOURCE AREA
BY 6-9-85