

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Jack A. Cole

3. ADDRESS OF OPERATOR

P.O. Box 191, Farmington, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 800' FNL, 880' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☒

☐

☐

☐

☐

☐

☐

☐

☐

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

RECEIVED

OCT 29 1986

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

See Attached for Casing and Cement Summary

RECEIVED

NOV 04 1986

OIL CON. DIV.]
DIST. 3

ACCEPTED FOR RECORD

NOV 03 1986

FARMINGTON RESOURCE AREA

BY ES

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dwaine Blanchett TITLE Production Superintendent DATE October 27, 1986

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCO

Cole Production Co.

(505) 325-1415
P.O. Box 191
3001 Northridge Dr.
Farmington, New Mexico 87499

MARCUS 'A' NO. 15

CASING AND CEMENT SUMMARY

10-22-86 TD 5580. Ran 135 joints, $4\frac{1}{2}$ ", 10.50 lb., K-55 casing.
Measured 5561.74, set at 5573.74.
Float collar-5514.56. Stage collar-2141.89.

Cemented 1st. stage with 10 bbls. mud flush followed by 120 sacks, (317 cu. ft.), 65-35 pozmix, 12% Gel and $6\frac{1}{4}$ lbs. Gilsonite per sack, followed by 150 sacks, (213 cu. ft.), 50-50 pozmix, 2% Gel, $6\frac{1}{4}$ lbs. Gilsonite and 6 lbs. salt per sack. Plug down 1:00 P.M. October 22, 1986. Calculated top of cement 3540'. Circulate 4 hours between stages.

Cemented 2nd. stage with 10 bbls. mud flush followed by 285 sacks, (752 cu. ft.), 65-35 pozmix, 12% Gel, $6\frac{1}{4}$ lbs. Gilsonite per sack, followed with 50 sacks (59 cu. ft.) Class B cement. Plug down 5:45 P.M. October 22, 1986. Circulated cement to surface.