

SUNDRY NOTICES AND REPORTS ON WELLS

(Use for: use this form for proposals to drill or to deepen or plug back to a well or for other purposes. Use "APPLICATION FOR PERMIT" for each proposal.)

☒ CAS
☐ WELL
☐ OTHER

NAME OF OPERATOR

Chace Oil Company

ADDRESS OF OPERATOR

313 Washington SE, Albuquerque, NM 87108

LOCATION OF WELL (Report location clearly and in accordance with any State requirements or any space 17 below.)

Unit 'H' 2064' FNL and 358' FEL

DEPTH IN

11 ELEVATIONS (Show whether in, on, or out)

7437' GR

Jicarilla Apache

Jicarilla Apache

UNIT AGREEMENT NAME

NAME OF LEASE NAME

Jicarilla Tribal Contract #47

WELL NO.

47-19

20 FIELD AND POOL, OR WELLS

South Lindrith Gallup-Dakota

11 SEC. T. R. S. OR B.L. AND SURVEY OR AREA

Sec. 11, T23N, R4W

12 COUNTY OR PARISH

13 STATE

Rio Arriba

New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

FAST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON

REPAIR WELL

CHANGE PLANT

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT

(Other)

Plug back

(Note: Report results of multiple completions on Well Completion or Recombination Report and Log form.)

LEADERS PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.)

9/29/87 8:50 A.M. Arapahoe Drilling Company contacted Frank Welker on his mobile phone and informed him that top of cement from plug back job was found at 377' KB and that the cement from 377' KB to 500' KB did not set up properly. Arapahoe decided to once more plug back open hole to surface casing. At 9:25 A.M. Chace attempted to notify the BLM of the second plug back job but found that the line was busy.

10:32 A.M. Set a cement plug from 500' KB to 180' KB with 150 sks (177 ft³) Class B Neat, 2% Calcium Chloride

RECEIVED
OCT 06 1987
OIL CON. DIV.
DIST. 2

I hereby certify that the foregoing is true and correct

SIGNED Frank Welker TITLE Vice President Production DATE Sept. 30, 1987

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side