

10-70707-1-83
(Formerly 9-231)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

PERMIT IN TRIPLICATE
(Other instructions on reverse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

SF-078272

6. IF INDICATE DATE OF PERMIT

7. UNIT AGREEMENT DATE JUN 6 1988

8. FARM OR TRACT NAME OIL CON. DIV.

Dunn DIST. 3

9. WELL NO.

15

10. FIELD AND POOL OR WILDCAT

Undesignated Graneros/

Lybrook Gallup

11. SEC. T. R. M. OR BLK. AND SURVEY OR AREA

Sec 9 T23N R7W NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

BCO, Inc.

3. ADDRESS OF OPERATOR

135 Grant Avenue, Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)
At surface

745' FSL and 790' FWL
Section 9 T 23N R7W NMPM
Rio Arriba County, N.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 7130

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spudding

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

May 25, 1988

Advised Mark Kelly with the BLM that we intended to spud the well May 26, 1988, and that we intended to cement surface pipe at 4:00 - 6:00 p.m. on May 26, 1988.
(date) (time) (date)

May 26, 1988

Spudded well. Drilled 12-1/4" hole and ran 208' 23# 8-5/8" limited service surface pipe. DV 229 at 1/2°. Landed pipe at 220' and cemented with 158 sacks Class B 2% CaCl cement with 1/4 lbs flocele per sack. Cement was mixed at 15.6 lbs with a yield of 1.18 cubic feet per sack or a total of 186.44 cubic feet. Circulated 15 barrels of cement. Plug down at 5:15 p.m. on May 26, 1988.
(time) (date)

May 26, 1988

Waiting on cement.

18. I hereby certify that the foregoing is true and correct

SIGNED James P. Bennett

TITLE Office Manager

DATE May 27, 1988

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

JUN 02 1988

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

NMOCC