\* Submit 3 Copers to Appropriate
Dis. 2 Office

COME OF THE PROPERTY Energy, Minerals and Natural Resources Department

Form C-100 Revised 1-1-39

MT JUN 0 2 1989

P.O. Box 1980, Hobbs, NM 22240

OIL CONSERVATION DIVISION P.O. Box 2088

DISTRICTE

Santa Fe, New Mexico 87504-2088

| EL. | API NO. |       | <br> |  |
|-----|---------|-------|------|--|
| 30  | -039-   | 24359 |      |  |
|     |         |       |      |  |

P.O. Deswer DD, Astesia, NM \$2210

| DISTRICT III   | STATE K FEE  |
|--|--|
| 1000 Rio Brazos Rd., Aztec, NM 87410   | 6. State Oil & Gas Lesse No.<br>V-2258   |
| SUNDRY NOTICES AND REPORTS ON WELLS  |  |
| (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  | TO A 7. Lease Name or Unit Agreement Name  |
| · (FORM C-101) FOR SUCH PROPOSALS.)  | •  |
| L Type of Well:  | State "J"  |
| MET X MET OTHER  |  |
| 2. Name of Operator BCO, Inc.  | £ Well No.   |
| 3. Address of Operator   | 2. 9. Pool name or Wildest   |
| 135 Grant Avenue, Santa Fe, NM 87501   |  |
| 4. Well Location   | Lybrook Gallup Ext.  |
| Unit Letter J : 1805 Feet From The South Line and  | 1730 Feet From The East  |
| Series 16 Touris 23N No. 711   |  |
| Section 16 Township 23N Range 7W   | NMPM Rio Arriba Comy   |
| 7315 GR  | ~ <i>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</i>  |
| 11. :- Check-Appropriate Box to Indicate Nature of Notice  | - Parent - Other Day   |
|  |  |
|  | SUBSEQUENT-REPORT OF:  |
| PERFORM REMEDIAL WORK  | K ALTERING CASING =  |
|  | <del>_</del> -   |
| TEMPORARILY ABANDON CHANGE PLANS COMMENCE DR   | TING ONE : T THE AIR AND   |
| THE OF A STEP CASE OF THE OFFICE DA  |  |
|  | TILING OPNS. PLUG AND ABANDONIMENT  ND CEMENT JOB X  |
| PULL OR ALTER CASING CASING TEST AT COTHER:  12. Describe Proposed or Completed Operations (Clearly state all persinent details, and give pursinent details.)  | ND CEMENT JOB X  |
| PLILL OR ALTER CASING CASING TEST AT CTHER:  OTHER:  12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give partinent dates world) SEE RULE 1103.  | ND CEMENT JOB X  |
| PLIL OR ALTER CASING CASING TEST AND COTHER:  12. Describe Proposed or Completed Operations (Clearly state all partitions details, and give partitions details and give partitions details.  5/22/89 - 5/27/89 Drilled 7-7/8" hole to 5800'. Bits were   | ND CEMENT JOB X  including estimated date of starting any proposed  run as follows:  Avg.  |
| PLILL OR ALTER CASING CASING TEST AT CTHER:  OTHER:  12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give partinent dates world) SEE RULE 1103.  | ND CEMENT JOB X  including estimated date of starting any proposed  run as follows:  Avg.  |
| CASING TEST AT COTHER:    Casing Test At Cother:   Casing Test At Cother:    | ND CEMENT JOB X  including estimated date of sturing any proposed  run as follows: Avg.  |
| ### CASING TEST AND CASING TEST AND COTHER:    CASING TEST AND COTHER:   Casing Test And Cother:   Cother:   Cother:   Casing Test And Cother:   Cother:   Cother:   Casing Test And Cother:   Cother:   Cother:   Cother:   Casing Test And Cother:   Cother:   Cother:   Cother:   Casing Test And Cother:   Cother:   Cother:   Cother:   Cother:   Cother:   Casing Test And Cother:   Cother: | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 2142 122 1/8°   |
| ### CASING TEST AND CASING TEST AND COTHER:    Casing Test And Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Casing Test And | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 2142 122 1/8°   |
| ### CASING TEST AND CASING TEST AND COTHER:    CASING TEST AND COTHER:   COT | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 2142 122 1/8°   |
| ### CASING TEST AND CASING TEST AND COTHER:    Casing Test And Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Casing Test And Cothers:   Cothers:   Cothers:   Casing Test And | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 122 1/8° 1/2° 1/2° 1/3° 1   |
| CASING TEST AND   CASING TEST AND   COTHER:   CASING TEST AND   COTHER:      | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 2142 1/8° 1/2° 1 JUN 0 2 1989   |
| ### CASING TEST AT CASING   Casing Test At CASING TEST AT COTHER:   Casing Test At COTHER:   Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Casing T | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 122 1/8° 1/2° 1 JUN 02 1989  Log and  |
| ### CASING TEST A    CASING TEST A   COTHER:   | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 2142 122 1/8° 1/2°  JUN 02 1989  OIL CON. DIV Log and Log.  |
| ### CASING TEST AT CASING   Casing Test At CASING TEST AT COTHER:   Casing Test At COTHER:   Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Cother:   Casing Test At Cother:   Casing T | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 2142 122 1/8° 1/2°  JUN 02 1989  OIL CON. DIV Log and Log.  |
| ### CASING TEST AND COMPLETE CASING TEST AND CONTRET.    12 Describe Proposed or Completed Operations (Clearly state all persons details, and give particular datasets)   5/22/89 - 5/27/89   Drilled 7-7/8" hole to   5800". Bits were  | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 2142 122 1/8° 1/2°  JUN 02 1989  OIL CON. DIV Log and Log.  |
| ### CASING TEST AND COTHER:    CASING TEST AND COTHER:   | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 1/2° 1/2° 1/2° 1 1/2 |
| ### CASING TEST AND COMPLETE CASING TEST AND CONTRET.    12 Describe Proposed or Completed Operations (Clearly state all persons details, and give particular datasets)   5/22/89 - 5/27/89   Drilled 7-7/8" hole to   5800". Bits were  | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 1/2° 1/2° 1/2° 1 1/2 |
| ### CASING TEST AND COTHER:    CASING TEST AND COTHER:   | run as follows:  Feet Drilled Hour Deviation  228 114 1/4° 122 1/8° 1/2° 1 1/2°  |

mız.

SUPERVISOR DISTRICT

Original Signed by FRANK T. CHAVEZ

(This space for State Use)

ATROVED BY-

Operator: BCO, Inc.

> 135 Grant Avenue Santa Fe, NM 87501

## SUNDRY NOTICES AND REPORTS ON WELLS

Lease No: V-2258

Page Two

Ran 5792' 4 1/2" 11.6 J-55 casing. Tagged bottom at 5795. Landed casing at 5792'. Ran one stage cement job from T.D. to surface. Pumped 10 barrels water, 10 barrels CaCl<sub>2</sub> water, 10 barrels water, 20 barrels flocheck 2-1.

Washed out pumps and lines. Pumped  $10^{\circ}$  barrels purple-red dye water and  $3^{\circ}$ barrels water. Pumped lead cement. Mixed 1200 sacks 50/50 Class G Poz Mix with 4% Gel, 10% salt, 10% cal-seal, 10 pounds gilsonite per sack. Cement mixed at 12.7# with a yield of 1.8 cubic feet per sack or 2160 cubic feet (approximately 386 barrels of slurry). Pumped tail cement. Mixed  $150\,\cdot$ sacks Class G cement with 1% CaCl  $_2$ , 8# salt per sack, 6 1/4# gilsonite per sack and 1/2# Flocele per sack. Cement was mixed at 15.2# with a yield of

1.377 cubic feet per sack or 206 cubic feet (approximately 37 barrels slurry). Circulated approximately 60 barrels good cement slurry to surface. Plug did not bump with 90 barrels displacement. Held pressure until float

held.

5/28/89

5/29/89 Waiting on cement to harden and completion rig.