

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SF 078362

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McBee 7

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Lybrook Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 7 T23N R6W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Bannon Energy, Inc. c/o Holcomb Oil & Gas, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 2058, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

Unit C, 330' FNL x 2130' FWL

14. PERMIT NO.

API #30-039-24544

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6874' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

MULTIPLE COMPLETE

FEB 03 1990

CHANGE PLANS

OIL CON. DIV.

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing & Cement Summary

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directional, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

McBee 7-4

TD - 5702'. Ran 129 joints, 4 1/2", 11.6 lb., J-55 casing. Measured 5697', set at 5697'. Float collar - 5654' (KB), Stage collar - 3407' (KB). First stage cemented as follows:

Pump 10 bbls. fresh water, 10 bbls. CaCl₂ water, 10 bbls. fresh water, 12 bbls. Flocheck-21, 10 bbls. water spacer followed by 350 sacks, (637 cubic ft.) 65-35 pozmix, followed by 100 sx. 50/50 poz (140 cubic feet); 6% 6 1/4 lbs. Gilsonite and 6 lbs. salt per sack. Plug down.

Circulated cement by stage collar. Circulated 4 hours between stages.

Second stage - same spacer program as the first stage followed by 565 sacks. (1028 cubic ft.) 65-35 pozmix, 12% gel, 6 1/4 lbs. Gilsonite per sack followed by 50 sacks, (59 cubic ft.) Class "B" cement and circulated to surface. Plug down.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. J. Holcomb

TITLE

Agent, Bannon Energy

DATE

1-24-90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side