

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

5. Lease Designation and Serial No.

NMSF - 078272

6. If Indian, Allottee or Tribe Name

NA

7. If Unit or CA, Agreement Designation

NA

8. Well Name and No.

DUNN #19

9. API Well No.

30-039-25507

10. Field and Pool, or Exploratory Area

Lybrook Gallup

11. County or Parish, State

Rio Arriba, New Mexico

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

UNIVERSAL RESOURCES CORPORATION

3. Address and Telephone No.

1331-17th Street, Suite 300, Denver, CO 80202 303-672-6970

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1730' FNL; 510' FEL, SE/4 NE/4, Section 4, T23N-R7W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☒ Casing Repair  
☐ Altering Casing  
☐ Other SPUD

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

DUNN #19 WAS SPUD AT 6:00PM ON MAY 10, 1995.

5/11/95 - SURFACE CASING SET AT 320' KBM AND CEMENTED WITH 250 SACKS OF CLASS "G". TESTED CASING TO 1500 PSI FOR 30 MINUTES. PRESSURE TESTED PIPE AND BLIND RAMS, LINES, MANIFOLD, FLOOR VALVES AND ANCILLARY EQUIPMENT TO 5500 PSI FOR 3 MINUTES AND 2000 PSI FOR 10 MINUTES.

5/20/95 - RAN 5,729.32' OF 4-1/2", 11.6#, J-55, 8RD LT&C CASING CEMENTED AS FOLLOWS: FIRST STAGE: WITH 167 SACKS 65/35 POZ WITH 6% GEL AND 100 SACKS CLASS "G". DISPLACE WITH 20 BARRELS WATER AND 68 BARRELS MUD. GOOD RETURNS.

5/21/95 - SECOND STAGE: CEMENT THROUGH DV TOOL AT 4,576.82' KBM WITH 806 SACKS OF 65/35 POZ WITH 6% GEL AND 50 SACKS OF CLASS "G". DISPLACE WITH 71 BARRELS WATER. LAND PLUG AT 1300 PSI AND BUMP PLUG TO 2800 PSI TO CLOSE STAGE TOOL. GOOD RETURNS.

CASING LAND AT 5,740.82' KBM. RIG RELEASED ON MAY 21, 1995.

1c

14. I hereby certify that the foregoing is true and correct

Signed

Title COORDINATOR, ADMINISTRATION Date MAY 31, 1995

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

NMCCD

FARMINGTON DISTRICT OFFICE

RV