Form 3160-5 (November 1994)

Type of Well

Oil Well

Address

Name of Operator

Elm Ridge Resources, Inc.

1450' FSL & 1190' FWI Sec. 1-T23N-R3W

PO Box 189 Farmington, NM 87499

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

SUBMIT IN TRIPLICATE - Other instruction

Other

X Gas Well

Location of Well (Footage, Sec., T., R., M., or Survey Description)

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals:

FORM APPROVED OMB No. 1004-0135 Expires July 31 1996

5. /	ease	Serial No.	,	,	
------	------	------------	---	---	--

BIA #167

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

wa.	
UE.	
-	8. Well Name and No.
ير پر	Jicarilla Apache I #11
7	9. API Well No.
	30-039-26325

7. If Unit or CA/Agreement, Name and/or No.

10. Field and Pool, or Exploratory Area South Blanco Picture Cliffs

11. County or Parish, State

Rio Arriba, New Mexico

12 CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
_	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	X Other Drilling
	Change Plans	Plug and Abandon	Temporarily Abandon	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	

505-632-3476

Spud well 8/26/01. Drilled 12-1/4 hole to 280' KB. Ran 6 jts- 8-5/8, K-55 24#, STC casing - set @ 260.90' KB.. Cemented w/200 sx Class "B" cement, 3% CaCl, 1/4# Celloflake. Displace w/15 bbls H20. Plug down @ 3:05 PM. Circulate 15 bbls to surface. Drilled 7-7/8 to 3200' KB. TD reached @ 6:00 AM on 8/29/01. Ran 74 jts, 4-1/2, 10.5#, J-55 casing - set @ 3420.42' KB. Cemented first stage w/450 sx 65/35/POZ, 6% gel, 1/4# Flocele, 10# Gilsonite, 1% cc and 200 Class "H", .5% Halad, 5# Gilsonite, 1/4# Flocele, 1% cc.. Bump plug to 1625 PSI. Circulate 2 hours and 20 bbls to surface. Drop plug w/ 1660 PSI - plug held. Circulate 60 bbls to surface. Rig down cementers. Set slips. Cut off casing. Release rig. Install wellhead.

Deceint # 7000 1670 0010 0404 0384

Centified Return Receipt #	7000 1070 0010 0494 036	-		
14. I hereby certify that the foregoing	is true and correct			
Name (Printed/Typed) Trudy Grubelnik			Production	n Technician
Signature \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Isubel D	Date	Septemb	er 21, 2001
	THIS SPAC	E FOR FED	ERAL OR STATE USE	
Approved by	プ ^{**}		Title Control	Date 17 10
Conditions of approval, if any, are attac certify that the applicant holds legal or which would entitle the applicant to co	equitable title to those rights in the s	ot warrant or subject lease	Office AUFC	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

^{13.} Describe Proposed or Completed Operations (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones.

Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days Following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has Testing has been completed. determined that the site is ready for final inspection.)