

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-26510
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. NMSF-078272A
7. Lease Name or Unit Agreement Name Nageezi Federal
8. Well No. 3 No. 4
9. Pool name or Wildcat Lybrook Gallup
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6990' ungraded ground

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Questar Exploration and Production Company
3. Address of Operator 1331 17th Street, Suite 800 Denver, CO 80202	4. Well Location Unit Letter E : 2173 Feet From The North Line and 1639 Feet From The West Line Section 3 Township 23N Range 7W NMPM Rio Arriba County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6990' ungraded ground	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Rig released ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 6 jts 4 1/2", 11.6#, J-55 ST&C casing. Landed at 5694'. Cemented with 448 sacks Class B Poz 50/50 cement with 2% D20, 1/4#/sack D29, 0.275% D167, 2% D46, 0.1% D-65. Cemented second stage with 618 sacks 50-50 lead and 50 sacks Class G neat. Displaced 71 bbls water. Set slips 30,000 over string weight

Rig released on 12-29-00 at 3:30 a.m.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Gary Ohlman TITLE Sr. Petroleum Engineer DATE 12-29-00  
TYPE OR PRINT NAME Gary Ohlman TELEPHONE NO. \_\_\_\_\_

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERREN

DEPUTY OIL & GAS INSPECTOR, DIST. 43

JAN - 3 2001

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: