

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.

Santa Fe, NM 87505

OCT 2001

RECEIVED

OIL CON. DIV.

DIST. 3

Amended

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator

Elm Ridge Resources, Inc.

3. Address of Operator

PO Box 189 Farmington, NM 87499

4. Well Location

Unit Letter N 920 Feet From Th South Line and 1735 Feet From Th West Line
Section 16 Townshi 23N Range 6W NMPM Rio Arriba County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
6880 GR

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: Drilling ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JO ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent date, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well 7/28/01. Drilled 12-1/4 hole to 380' KB. Ran 8-jts 8-5/8, 24# J-55 STC casing - set @ 356.78' KB. Cemented w/250 sx Class "B", 3% CaCl, 1/4# Celloflake. Displace w/21.1 bbls H₂O. Plug down @ 8:30 PM. Circulate 10 bbls to surface. Drilled 7-7/8 to 5650' KB. TD reached @ 4:00 PM on 8/8/01. Ran 131-jts 4-1/2, 10.5#, J-55 casing - set @ 5650' KB. Stage tool set @ 2309' KB. Cemented first stage w/530 sx 65/35/POZ, 6% gel, 1/4# Flocele, 10# Gilsonite, 1% cc and 15 sx Class "H", 1% CaCl, 1/4# Flocele, 5# Gilsonite. Bump plug to 1650 PSI. Circulate 4 hours and 45 bbls to surface. Cement 2nd stage w/395 sx 65/35/POZ, 6% gel, 1/4# Flocele, 10# Gilsonite, 1% cc and 50 sx Class "H" cement. Drop plug and close stage tool w/2000 PSI - plug held. Circulate 10 bbls to surface. Rig down cementers. Set slips. Cut off casing. Release rig. Install wellhead. PBTD @ 5604' KB.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Trudy Grubelnik TITLE Production Technician DATE 10/26/01
TYPE OR PRINT NAME Trudy Grubelnik TELEPHONE NO. 505-632-3476 ext. 201

(This space for State Use)

APPROVED BY Chad R TITLE 2 GAS INSPECTOR DIST. 3 DATE OCT 29 2001
CONDITIONS OF APPROVAL, IF ANY: