Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
QMB No. 1004-0135
QMB No. 1004-0135 Expires July 31, 1996

5. Lease	Serial N	0.
----------	----------	----

From Service Community and Community	JREAU OF LAND MANAGE ' NOTICES AND REPORTS	70. \"		NMSF-078	
Do not use this	s form for proposals to	drill or teenter		· L	llottee or Tribe Name
SUBMIT IN TRIPL	. Use Form 3160-3 (APD) JCATE – Other instru	4	AST ON	7. If Unit or C.	A/Agreement, Name and/or No.
Type of Well Gas Well Gas Well	Other		Q19 5 3 200	8. Well Name	and No.
2. Name of Operator				Rincon #20	
Elm Ridge Resources, Inc.				9. API Well N	0.
3a. Address		3b. Phone No. (include	de area code)	30-039-267	68
PO Box 189 Farmington, NM 8	87499	505-632-3476		1	ool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R.	R., M., or Survey Description)			1	Ilup & Basin Dakota
1708' FSL & 1768' FWL				11. County or P	arish, State
Sec. 11-T23N-R7W				Rio Arriba,	New Mexico
12. CHECK APPROPRIATE BOX(E	ES) TO INDICATE NATURE	OF NOTICE, REPOR	RT, OR OTHER DA	TA	
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
	Alter Casing	Fracture Treat	Reclamation		Well Integrity
Subsequent Report	Casing Repair	New Construction			X Other Drilling
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporarily Water Dispo		
Testing has been completed. Final Abdetermined that the site is ready for final inspection. Spud well 8/10/01. Drill 12-1/4 Class "B" cement, 3% CaCl, 1 on 8/24/01. Ran Halliburton H J-55 casing - set @ 6656.70' K 10# Gilsonite, 1% cc and 290 s Bump plug 1200 PSI and open 6% gel, 1/4# Flocel, 10# Gilson close stage tool w/2420 PSI - prig. Install wellhead.	hole to 410' KB. Ran 9 1/4# Celloflake. Displace ligh Resolution Induction KB. Stage tool set @ 467 sx Class "H" cement, .5% n stage tool. Circulate 4 nite, 1% cc and 50 Sx Cl	jts-8-5/8 ,K-55, S ⁻ e w/25 bbls H20. E and Spectral Dua 75'. KB. Cemente 6 Halad, 5# Gilson hours and 3 bbls t lass "H", .5 Halad	TC casing - set @ Drilled 7-7/8 to 6 al Spaced Neutro ed first stage w/6 nite, 1/4# Gilsoni to surface. Cem , 9-5# Gilsonite,	2) 387.42' KE 650' KB. TD on Log. Ran 5/35/POZ - 6 ite 1% cc. D ent 2nd stag 1/4# Folcele	3 Cemented w/ 275 sx reached @ 11:45 AM 154 jts 4-1/2, 10.5 #, 5% gel, 1/4# Flocele, isplace w/30 bbls H20. e w/579 sx 65/35/POZ- , 1% cc. Drop plug and
Certified Return Receit # 7000			-		
14. I hereby certify that the foregoing is tr	rue and correct	Title			
Name (Printed/Typed) Trudy G	Srubelnik	1100	Droduct	ion Technici	an
		1	Fibuuci		GII
Signature \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Shu boh D	Date		nber 21, 200	
	Supoh D	Date FOR FEDERAL OR'S	Septer		
	Supoh D		Septer		

20 2001

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Elm Ridge Resources, Inc. Rincon #20 Sec. 11-T23N-R7W Rio Arriba, New Mexico

SLOPE TESTS

DEPTH	· •	HOLE DEVIATION
93'		1/4
212'		3/4
304'	•	1/4
400'		1/4
917'		1/4
1404'		3/4
1901'		1
2394'		3/4
2919		1
3420'		3/4
3922'		1
4425'		1
4918'	and the state of t	1
5353'		1
5840'		1
6340'		1
6650'		1-1/4

State of New Mexico)

SS

County of San Juan)

I, <u>Trudy Grubelnik</u>, being first duly sworn, depose and state that the above and foregoing depth and hole deviation figures are true and correct to the best of my information and belief.

Subscribed and sworn before me this 21st day of September, 2001.

Notary Public

My commission Expires 22,05