

Form 100-10
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
TO THE GEOLOGICAL SURVEY
WASHINGTON, D. C. 20508

Form approved
Budget Project No. 42 H1424
LEASE DESIGNATION AND SERIAL NO.

Contract No. 160

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla G 160

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

So Blanco PC

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

14 - 23N - 2W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Dry Hole

2. NAME OF OPERATOR
Shar-Alan Oil Company

3. ADDRESS OF OPERATOR
1402 Denver U. S. National Center, Denver, Colorado 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1850' from the South line and 1850' from the West line

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 7258.4

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

XXXX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Intend to pull 4 1/2" casing. Spot approximately 60 sacks of cement at total depth and set cement plugs at bottom of surface casing and at the top of hole with 20 sacks of cement. Set dry hole marker and restore location.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE Mgr. of Lands & Explorations DATE 8-25-66


APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side



U. S. GEOLOGICAL SURVEY