



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Farmington
Lease No. 2M 010319
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Surface Casing</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 8, 1960

Ohio Government Mines

Well No. 1 is located 990 ft. from SW line and 990 ft. from SE line of sec. 20

N2 SW SW Sec. 20
(1/4 Sec. and Sec. No.)

15N
(Twp.)

1E
(Range)

(Meridian)

Cornfield Canyon
(Field)

Sandoval
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the ~~derrick floor~~ ^{ground} above sea level is 3761 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 10-27-60.

Ran 10 jts. 13-3/8" casing set from 14.0' to 363.38'. Cemented with 300 sacks 50-50 permix. Displaced with 36 BW. Plug down at 1:00 PM 11-3-60. Fair returns. WOC. Pressured casing to 3000. Held OK.

3 jts. 13-3/8" 48# 8rd H-40 ST&C
7 jts. 13-3/8" 54.5# 8rd J-55 ST&C
1 - 13-3/8" Baker Guide Shoe



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE OHIO OIL COMPANY

Address P. O. Box 120

Casper, Wyoming

By

[Signature]

Title Division Production Superintendent