

WEEK ENDING 12-9-61

CORE FROM 6930

TO

CORES EXAMINED BY Sisler

SHELL OIL COMPANY

AREA OR FIELD Wildcat

COMPANY Shell

CORE RECORD

LEASE AND WELL NO. Wright 41-26

NO.	FROM	TO	RECOVERED	FORMATIONAL, STRUCTURAL AND PROBABLE PRODUCTIVITY DESCRIPTION OF CORE	SYMBOL	OBSERVED DIP	CORE INDICATIONS	
							OIL-GAS	CORE OR DITC
1	6930	6952	19	Granite, pink-gray, coarsely crystalline, 40 per cent quartz, 20 per cent plagioclase, 30 per cent K-feldspar, 10 per cent muscovite, biotite and hornblende, fractures 60° from vertical, spaced 1'-2' apart	- Granite	--		None
				Coring Rate - Diamond Tri Di Bit C-17384 Min/Ft.				
				6930 - 6931				
				32				
				33				
				34				
				6934 - 6935				
				36				
				37				
				38				
				39				
				6939 - 6940				
				41				
				42				
				43				
				44				
				6944 - 6945				
				46				
				47				
				48				
				49				
				6949 - 6950				
				51				
				52				
				110 (Wedged in Bbl.)				
				Coring Engineer Joe Hemphill Drilling & Service, Inc.				

SYMBOLS: C-CLAY OR SHALE (SAND 0-5%). 1-CLAY OR SHALE WITH SAND STREAKS (SAND 5-25%). 2-CLAY OR SHALE AND SAND (SAND 25-60%). 3-SAND WITH SHALE STREAKS (SAND 60-90%). S-SAND (90-100%).
NOTE: SHOW FLUID CONTENT AS IN STANDARD LEGEND.