

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 021478 (term.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box EE, Cortez, Colorado 81321

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Moore

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

S-22 - 19N - 3W

12. COUNTY OR PARISH 13. STATE

Sandoval

N. Mex.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DIS. RILE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

8-20-77

Ran 53 joints of 2 7/8 8rd. EUE Tbnng. tagged at 1655 GL.

8-21-77

Set 15 sx. cement plug 1653' - 1494'. Pulled and layed down 5 jts. tbnng. Waited on cement 1 hour filled hole with water. level did not go down. Plug held, pulled and layed down 31 jts. tbnng. Set 18 sx. cement plug 507 - 357'. Pulled and layed down 16 jts. tbnng., set 25 sx. cement plug 30' to surface in 12" and 5½" csg. Set and welded dry hole marker. Well location needs to be cleaned up.

18. I hereby certify that the foregoing is true and correct

SIGNED

Alvin R. May Jr.

TITLE

Field Foreman

DATE

8-24-77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side