

COPY FOR  
STATE OF NEW MEXICO  
OIL CONSERVATION  
COMMISSION  
SUBMIT IN TRIPLICATE TO  
DISTRICT OFFICE

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_

Lease No. SF 078939-D

Unit \_\_\_\_\_

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

MAR 22 1954  
U. S. GEOLOGICAL SURVEY  
FARMINGTON N. M.

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 18, 1954

Renkoff "D"  
Well No. #1 is located 1980 ft. from NS line and 1980 ft. from TSW line of sec 17  
NE SW - 17 19N 4W NMPM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wildcat Sandoval New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Well had levelled off to 3 barrels of oil & 20 barrels water per day; well was then deepened to 2220' TD without encountering commercial production but encountered salt water at 2209'. Therefore, authority is requested to plug and abandon well.

It is intended to spot cement plug 2220-2100' & cement plug from 1750-1600' & from 300-200'. 7" casing is set at 2104' without cement; 8-5/8" set @ 1670' w/65 sks cement. It is intended to pull 7" & recover as much 8-5/8" as possible. Cement plug will be placed in top of 13-3/8" surface csg. A marker on top is to be not less than 4" pipe & not less than 10' long, of which 4' shall be above ground & the remainder in cement. The top of pipe to be closed with cap or cement & a plate installed on pipe to show as follows:

"Tim G. Lowry, Lowry-Renkoff D, 1980 FS&W 17-19N-4W, Well: Renkoff D-1"

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Tim G. Lowry, dba Lowry et al Operating Account

Address Box 8008

Albuquerque, N.M.

By E. R. Richardson  
E. R. Richardson  
Title Assistant General Mgr.