

(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

Allotted

Allottee Ulin-hos-pah Tomas

Lease No. 14-20-03-58

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY


SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 13

1956

Well No. 1 is located 990 ft. from N line and 990 ft. from E line of sec. 22  
NE 1/4 Sec. 22 22-North 6-West H.M. P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wildcat Sandoval New Mexico  
(Field) (County or Subdivision) (State or Territory)


The elevation of the derrick floor above sea level is 7073 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

To Plug & Abandon Well.

A 100' cement plug has been set from 6325-6425.  
 100' of 10-3/4" 32.75# casing cemented w/175 sx & circulated. To be left in hole. 6310' of 15.50# 5 1/2" casing cemented w/250 sx to be left in hole. A cement plug to be set from surface to 92' w/approx. 50 sx & space between 5 1/2" and 10-3/4" casing to be filled with cement.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company PLYMOUTH OIL COMPANY  
 Address 340 Silver State Building  
Denver 2, Colorado  
 By [Signature]  
Regional Supervisor  
 Title \_\_\_\_\_