

|  |    |   |  |
|--|----|---|--|
|  |    |   |  |
|  | 23 |   |  |
|  |    | X |  |
|  |    |   |  |

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **SANTA FE**  
Lease No. **SF 080097**  
Unit **I**

SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |   |  |
|---|---|---|--|
| NOTICE OF INTENTION TO DRILL.....                   |   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |  |
| NOTICE OF INTENTION TO CHANGE PLANS.....            |   | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     |   | SUBSEQUENT REPORT OF ALTERING CASING.....       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... |   | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        |   | SUBSEQUENT REPORT OF ABANDONMENT.....           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    |   | SUPPLEMENTARY WELL HISTORY.....                 |  |
| NOTICE OF INTENTION TO ABANDON WELL.....            | X |   |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 18, 1964

**Sandoval**  
Well No. **1-23** is located **1980** ft. from **S** line and **660** ft. from **E** line of sec. **23**  
**NE 1/4 Sec. 23** (1/4 Sec. and Sec. No.)  
**Undesignated Gallup** (Field)  
**22N** (Twp.)  
**7W** (Range)  
**N 100° E** (Meridian)  
**Sandoval** (County or Subdivision)  
**New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **6812** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

TD 5880. PB TD 5795. Propose to spot 17 sz cement plug in 5 1/2" OD casing from 4653 to 4789 to plug off Gallup. Salvage as much 5 1/2" casing as possible, plug 5 1/2" casing stub from 50' below top of stub to 50' above top of stub. Plug Lewis and Chacra formation with cement from 1700 to 1550; plug Pictured Cliffs with cement from 1300 to 1150. Plug top of 10-3/4" surface pipe with cement and place dry hole marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **NORTHWEST PRODUCTION CORPORATION**

Address **BOX 1796**

**EL PASO, TEXAS 79949**

By \_\_\_\_\_

Title **J. M. Newman, Mgr., Prod. Oper.**

...the ... of ...

...the ... of ...

...the ... of ...

...the ... of ...

...the ... of ...

...the ... of ...

...the ... of ...

...the ... of ...

...the ... of ...