

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency

Jicarilla Apache

Allottee Superior Oil Company

Lease No. Tribal 74

APPROVED
MAR 6 1955
101st Sgd. P. T. McGRATH
DISTRICT ENGINEER
Sec. 10

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 7, 1956

Well No. 2 is located 999 ft. from $\begin{matrix} N \\ S \end{matrix}$ line and 990 ft. from $\begin{matrix} E \\ W \end{matrix}$ line of sec. 10

SW NE NE, Sec. 10
(1/4 Sec. and Sec. No.)

22N
(Twp.)

3W
(Range)

N. M. P. M.
(Meridian)

Wildcat
(Field)

Sandoval
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 2590 ft. G. L. ; 2600 D. F.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Plan to set cement plugs with 75 sacks from 2602 feet to 2450 feet, 25 sacks from 250 feet to 85 feet, 10 sacks in surface, and pour concrete 2 feet square and 1 foot high over surface pipe.

Verbal approval by phone 3/6/56.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company CASHWELL SILVER

Address 323 Simms Building

Albuquerque

New Mexico

By

Cashwell Silver

Title

Operator